



## DESCRIPTION

BALEEN ATM is a high quality, mild-EP automotive gear lubricant designed for applications where API GL-4 performance is required. The oil is made from highly refined base oil and selected additives to provide good oxidation stability to resist oil degradation and thickening in service. The special mild-EP additive and corrosion inhibitor is non-corrosive towards sensitive copper alloy components and protects ferrous metals against rusting in the presence of moisture. BALEEN ATM meets and exceeds the performance requirement of API GL-4, MIL-L-2105B and CS 3000A and is environmentally responsible, containing neither lead nor chlorine.

## FEATURES AND BENEFITS

- Excellent load-carrying capacity
- Outstanding rust and corrosion properties
- Improved anti-wear properties
- Excellent thermal and oxidation stability

## APPLICATION

BALEEN ATM is suitable for automotive spiral-bevel axles, steering gears, tractors and agricultural gear sets, oil lubricated track rollers of crawler tractors and industrial applications for which API GL-4 performance oils are required.

### TYPICAL SPECIFICATION

SAE GRADE		90	140	80W/90	85W/140
Kinematic Viscosity at 40°C (cSt)	ASTM D445	196	460	157	425
Kinematic Viscosity at 100°C (cSt)	ASTM D445	18	30.5	16	30
Viscosity Index	ASTM D2270	96	95	101	97
Flash Point COC (°C)	ASTM D92	205	223	200	218
Pour Point (°C)	ASTM D97	-10	-9	-25	-20